



SECTION A-A

REVISION NOTES AND DATES

UNLESS OTHERWISE SPECIFIED:

ALL DIMENSIONS ARE IN INCHES
 TOLERANCES AS FOLLOWS:
 1 PLACE DECIMAL (.0): ±.030
 2 PLACE DECIMAL (.00): ±.020
 3 PLACE DECIMAL (.000): ±.010
 ANGLES: ±2°

SURFACE FINISH: 63RMS
 BREAK ALL EDGES: .010-.015
 FILLETS & ROUINDS: R.015 - 0.30

THREADS UNIFIED CLASS 2A - 2B
 CHAMFER THREADS 45° TO ROOT
 30° CHAMFER IS OPTIONAL
 FOR MALE THREADS ONLY

	NAME	DATE
DRAWN	BM	10/09/2024
CHECKED	KH	10/09/2024
DATE STARTED IN PRODUCTION:		
10/09/2024		



**ULTRA PRESSURE COMPONENTS
 HOUSTON, TX**

TITLE:
 1/4" NPT Female Bulkhead
 15,000 psi

SIZE A	DWG. NO. 5000-4N4N-BH	REV Y
------------------	--------------------------	-----------------

SCALE: 1.5:1 | WEIGHT: 0.30 | SHEET 1 OF 1

PROPRIETARY AND CONFIDENTIAL
 THE INFORMATION CONTAINED IN THIS
 DRAWING IS THE SOLE PROPERTY OF
 ULTRA PRESSURE COMPONENTS. ANY
 REPRODUCTION IN PART OR AS A WHOLE
 WITHOUT THE WRITTEN PERMISSION OF
 ULTRA PRESSURE COMPONENTS IS
 PROHIBITED.