



**SECTION A-A**

UNLESS OTHERWISE SPECIFIED:

ALL DIMENSIONS ARE IN INCHES  
 TOLERANCES AS FOLLOWS:  
 1 PLACE DECIMAL (.0): ±.030  
 2 PLACE DECIMAL (.00): ±.020  
 3 PLACE DECIMAL (.000): ±.010  
 ANGLES: ±2°

SURFACE FINISH: 63RMS  
 BREAK ALL EDGES: .010-.015  
 FILLETS & ROUNDINGS: R.015 - 0.30

THREADS UNIFIED CLASS 2A - 2B  
 CHAMFER THREADS 45° TO ROOT  
 30° CHAMFER IS OPTIONAL  
 FOR MALE THREADS ONLY

	NAME	DATE
DRAWN	BM	8/23/24
CHECKED	KH	8/23/24
DATE STARTED IN PRODUCTION:		
8/23/24		



**ULTRA PRESSURE COMPONENTS  
 HOUSTON, TX**

TITLE:  
 1/8"-27 NPT Hollow Hex Plug  
 15,000 psi

SIZE <b>A</b>	DWG. NO. 5406P-HH-2N	REV <b>Y</b>
------------------	-------------------------	-----------------

SCALE: 5:1    WEIGHT: 0.01    SHEET 1 OF 1

REVISION NOTES AND DATES

**PROPRIETARY AND CONFIDENTIAL**

THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF ULTRA PRESSURE COMPONENTS. ANY REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION OF ULTRA PRESSURE COMPONENTS IS PROHIBITED.