



SECTION A-A

REVISION NOTES AND DATES	UNLESS OTHERWISE SPECIFIED: ALL DIMENSIONS ARE IN INCHES TOLERANCES AS FOLLOWS:		NAME	DATE	ULTRA PRESSURE COMPONENTS HOUSTON, TX	
	1 PLACE DECIMAL (.0): ±.030 2 PLACE DECIMAL (.00): ±.020 3 PLACE DECIMAL (.000): ±.010 ANGLES: ±2°		DRAWN	BM 10/31/2022		TITLE: HPC600 Nipple x 3/4" MP Male 20,000 psi
	SURFACE FINISH: 63RMS BREAK ALL EDGES: .010-.015 FILLETS & ROUNDS: R.015 - 0.30		CHECKED	KH 09/06/2024		
	THREADS UNIFIED CLASS 2A - 2B CHAMFER THREADS 45° TO ROOT 30° CHAMFER IS OPTIONAL FOR MALE THREADS ONLY		DATE STARTED IN PRODUCTION: 09/06/2024			SIZE
				A	HPC600-1-12MM	Y
				SCALE: 1.5:1	WEIGHT: 1.41	SHEET 1 OF 1

PROPRIETARY AND CONFIDENTIAL
THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF ULTRA PRESSURE COMPONENTS. ANY REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION OF ULTRA PRESSURE COMPONENTS IS PROHIBITED.