			-					
PROPRIETARY AND CONFIDENTIAL	REVISION NOTES AND DATES	UNLESS OTHERWISE SPECIFIED: ALL DIMENSIONS ARE IN INCHES TOLERANCES AS FOLLOWS: 1 PLACE DECIMAL (.0): ±.030 2 PLACE DECIMAL (.00): ±.020 3 PLACE DECIMAL (.000): ±.010 ANGLES: ±2° SURFACE FINISH: 63RMS BREAK ALL EDGES: .010015 FILLETS & ROUINDS: R.015 - 0.30				HO TITLE: HPC6	C600 x 1" MP Male 20,000 psi	
THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF ULTRA PRESSURE COMPONENTS. ANY REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION OF ULTRA PRESSURE COMPONENTS IS PROHIBITED.	↑4	THREADS UNIFIED CLASS 2A - 28 CHAMFER THREADS 45° TO ROOT 30° CHAMFER IS OPTIONAL FOR MALE THREADS ONLY 3	ultra		an handle Pressure		600-1-16MN	A REV SHEET 1 OF 1