



### SECTION A-A

REVISION NOTES AND DATES	UNLESS OTHERWISE SPECIFIED:		NAME	DATE	<b>ULTRA PRESSURE COMPONENTS HOUSTON, TX</b>	
	ALL DIMENSIONS ARE IN INCHES TOLERANCES AS FOLLOWS: 1 PLACE DECIMAL (.0): ±.030 2 PLACE DECIMAL (.00): ±.020 3 PLACE DECIMAL (.000): ±.010 ANGLES: ±2°		DRAWN	BM 9/27/24		
	SURFACE FINISH: 63RMS BREAK ALL EDGES: .010-.015 FILLETS & ROUNDINGS: R.015 - 0.30		CHECKED	KH 9/27/24	TITLE:	
	THREADS UNIFIED CLASS 2A - 2B CHAMFER THREADS 45° TO ROOT 30° CHAMFER IS OPTIONAL FOR MALE THREADS ONLY		DATE STARTED IN PRODUCTION:		HPC600 Nipple x 1/4" HP Female 30,000 psi	
<p><b>PROPRIETARY AND CONFIDENTIAL</b></p> <p>THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF ULTRA PRESSURE COMPONENTS. ANY REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION OF ULTRA PRESSURE COMPONENTS IS PROHIBITED.</p>		9/27/24		SIZE	DWG. NO.	REV
				<b>A</b>	HPC600-1-4HF-WO	<b>Y</b>
				SCALE: 1.5:1		WEIGHT: 0.33