







| | | UNLESS OTHERWISE SPECIFIED: | | NAME | DATE | ULTRA PRESSURE COMPONENTS |
|---|--------------------------|---|---|--------------|-------------------|---|
| | REVISION NOTES AND DATES | 1) DIMENSIONS ARE IN INCHES 2) TOLERANCES: FRACTIONAL± 1/64" ANGULAR: MACH± 2° ONE PLACE DECIMAL±.020 | DRAWN | MH KH | 10/20/2017 | · |
| | | | CHECKED DATE STA | ARTED IN PRO | | - I III CE. |
| | | TWO PLACE DECIMAL ± .010 THREE PLACE DECIMAL ± .005 | 10/20/2017 | | 017 | HPC600 Nipple x 1/4" JIC Male 15,000 psi |
| PROPRIETARY AND CONFIDENTIAL | | 3) THREADS UNIFIED CLASS 2A - 2B 4) SURFACE FINISH 63uin Ra 5) CHAMFER THREADS: MALE - 30° TO ROOT FEMALE - 45° TO ROOT | utra Pressure components We can handle Pressure | | | |
| THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF ULTRA PRESSURE COMPONENTS. ANY REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION OF | | | | | | A HPC600-1-4JM Y |
| ULTRA PRESSURE COMPONENTS IS PROHIBITED. | | | | | n handle Pressure | SCALE: 1.5:1 WEIGHT: 0.13 SHEET 1 OF 1 |

5 4 3 2