



**SECTION A-A**

REVISION NOTES AND DATES	UNLESS OTHERWISE SPECIFIED:		NAME	DATE	<b>ULTRA PRESSURE COMPONENTS HOUSTON, TX</b>	
	ALL DIMENSIONS ARE IN INCHES TOLERANCES AS FOLLOWS:		DRAWN	BM		9/26/24
	1 PLACE DECIMAL (.0): ±.030		CHECKED	KH		9/26/24
	2 PLACE DECIMAL (.00): ±.020		DATE STARTED IN PRODUCTION:			TITLE: HPC600 Nipple x 1/4" NPT Male 15,000 psi
	3 PLACE DECIMAL (.000): ±.010		9/26/24			
ANGLES: ±2°						
SURFACE FINISH: 63RMS		SIZE	DWG. NO.		REV	
BREAK ALL EDGES: .010-.015		<b>A</b>	HPC600-1-4NM		<b>Y</b>	
FILLETS & ROUNDINGS: R.015 - 0.30		SCALE: 1.5:1		WEIGHT: 0.15	SHEET 1 OF 1	
THREADS UNIFIED CLASS 2A - 2B						
CHAMFER THREADS 45° TO ROOT						
30° CHAMFER IS OPTIONAL FOR MALE THREADS ONLY						

**PROPRIETARY AND CONFIDENTIAL**  
 THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF ULTRA PRESSURE COMPONENTS. ANY REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION OF ULTRA PRESSURE COMPONENTS IS PROHIBITED.