







	UNLESS OTHERWISE SPECIFIED:
	ALL DIMENSIONS ARE IN INCHES
REVISION NOTES AND DATES	TOLERANCES AS FOLLOWS:
	1 PLACE DECIMAL (.0): ±.030
	2 PLACE DECIMAL (.00): ±.020
	3 PLACE DECIMAL (.000): ±.010
	ANGLES: ±2°
	CUREA OF FIVIRITY (ORVICE

SURFACE FINISH: 63RMS BREAK ALL EDGES: .010-.015 FILLETS & ROUINDS: R.015 - 0.30

THREADS UNIFIED CLASS 2A - 2B CHAMFER THREADS 45° TO ROOT 30° CHAMFER IS OPTIONAL FOR MALE THREADS ONLY

	NAME	DATE
DRAWN	ВМ	10/03/2024
CHECKED	KH	10/03/2024
DATE STARTED IN PRODUCTION:		

10/03/2024

## ULTRA PRESSURE COMPONENTS HOUSTON, TX

TITLE:

SECTION A-A

HPC600 Nipple x 3/8" JIC Male 15,000 psi

SIZE DWG. NO. **REV** HPC600-1-6JM SCALE: 1.5:1 WEIGHT: 0.14 SHEET 1 OF 1

ULTRA PRESSURE COMPONENTS. ANY REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION OF ULTRA PRESSURE COMPONENTS IS PROHIBITED.

5

PROPRIETARY AND CONFIDENTIAL THE INFORMATION CONTAINED IN THIS

DRAWING IS THE SOLE PROPERTY OF

3

2