



SECTION A-A

REVISION NOTES AND DATES

UNLESS OTHERWISE SPECIFIED:

ALL DIMENSIONS ARE IN INCHES
 TOLERANCES AS FOLLOWS:
 1 PLACE DECIMAL (.0): ±.030
 2 PLACE DECIMAL (.00): ±.020
 3 PLACE DECIMAL (.000): ±.010
 ANGLES: ±2°

SURFACE FINISH: 63RMS
 BREAK ALL EDGES: .010-.015
 FILLETS & ROUNDINGS: R.015 - 0.30

THREADS UNIFIED CLASS 2A - 2B
 CHAMFER THREADS 45° TO ROOT
 30° CHAMFER IS OPTIONAL
 FOR MALE THREADS ONLY

	NAME	DATE
DRAWN	MH	07/23/2024
CHECKED	KH	07/23/2024
DATE STARTED IN PRODUCTION:		
07/23/2024		

**ULTRA PRESSURE COMPONENTS
 HOUSTON, TX**

TITLE:
 HPC600 Nipple x 3/8" MP Male
 20,000 psi

SIZE A	DWG. NO. HPC600-1-6MM	REV Y
------------------	--------------------------	-----------------

SCALE: 1.5:1	WEIGHT: 0.15	SHEET 1 OF 1
--------------	--------------	--------------



PROPRIETARY AND CONFIDENTIAL
 THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF ULTRA PRESSURE COMPONENTS. ANY REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION OF ULTRA PRESSURE COMPONENTS IS PROHIBITED.