| 6000   |                          |   |  |  |   |  |
|--|--------------------------|---|--|--|---|--|
|  |                          |   | 3/8"-18NPT<br>Male Thread                                |  |   |  |
|  | REVISION NOTES AND DATES | UNLESS OTHERWISE SPECIFIED:<br>ALL DIMENSIONS ARE IN INCHES<br>TOLERANCES AS FOLLOWS:<br>1 PLACE DECIMAL (.0): ±.030<br>2 PLACE DECIMAL (.00): ±.020<br>3 PLACE DECIMAL (.000): ±.010<br>ANGLES: ±2°<br>SURFACE FINISH: 63RMS<br>BREAK ALL EDGES: .010015 | DRAWN BM<br>CHECKED KH<br>DATE STARTED IN PRO<br>9/27/24 | DATE<br>9/27/24<br>9/27/24<br>DUCTION: | ULTRA PRESSURE COMPONENTS<br>HOUSTON, TX<br>TITLE:<br>HPC600 Nipple x 3/8" NPT Male<br>15,000 psi |  |
| PROPRIETARY AND CONFIDENTIAL<br>THE INFORMATION CONTAINED IN THIS<br>DRAWING IS THE SOLE PROPERTY OF<br>ULTRA PRESSURE COMPONENTS. ANY<br>REPRODUCTION IN PART OR AS A WHOLE<br>WITHOUT THE WRITTEN PERMISSION OF<br>ULTRA PRESSURE COMPONENTS IS<br>PROHIBITED. | ^                        | FILLETS & ROUINDS: R.015 - 0.30<br>THREADS UNIFIED CLASS 2A - 2B<br>CHAMFER THREADS 45° TO ROOT<br>30° CHAMFER IS OPTIONAL<br>FOR MALE THREADS ONLY   | UltraPress<br>Wecan                                      | handle Pressure                        | SIZE DWG. NO. REV   A HPC600-1-6NM Y   SCALE: 1.5:1 WEIGHT: 0.16 SHEET 1 OF 1   1 1               |  |