



SECTION A-A

REVISION NOTES AND DATES

UNLESS OTHERWISE SPECIFIED:

ALL DIMENSIONS ARE IN INCHES  
 TOLERANCES AS FOLLOWS:  
 1 PLACE DECIMAL (.0): ±.030  
 2 PLACE DECIMAL (.00): ±.020  
 3 PLACE DECIMAL (.000): ±.010  
 ANGLES: ±2°

SURFACE FINISH: 63RMS  
 BREAK ALL EDGES: .010-.015  
 FILLETS & ROUNDINGS: R.015 - 0.30

THREADS UNIFIED CLASS 2A - 2B  
 CHAMFER THREADS 45° TO ROOT  
 30° CHAMFER IS OPTIONAL  
 FOR MALE THREADS ONLY

|                             | NAME | DATE    |
|-----------------------------|------|---------|
| DRAWN                       | BM   | 9/27/24 |
| CHECKED                     | KH   | 9/27/24 |
| DATE STARTED IN PRODUCTION: |      |         |
| 9/27/24                     |      |         |



**ULTRA PRESSURE COMPONENTS  
 HOUSTON, TX**

TITLE:  
 HPC600 Nipple x 9/16" HP Female  
 30,000 psi

|                  |                             |                 |
|------------------|-----------------------------|-----------------|
| SIZE<br><b>A</b> | DWG. NO.<br>HPC600-1-9HF-WO | REV<br><b>Y</b> |
|------------------|-----------------------------|-----------------|

SCALE: 1:1    WEIGHT: 0.55    SHEET 1 OF 1

**PROPRIETARY AND CONFIDENTIAL**  
 THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF ULTRA PRESSURE COMPONENTS. ANY REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION OF ULTRA PRESSURE COMPONENTS IS PROHIBITED.