







## SECTION A-A

		UNLESS OTHERWISE SPECIFIED: ALL DIMENSIONS ARE IN INCHES		NAME	DATE	ULTRA PRES			
	REVISION NOTES AND DATES	TOLERANCES AS FOLLOWS:  1 PLACE DECIMAL (.0): ±.030  2 PLACE DECIMAL (.00): ±.020  3 PLACE DECIMAL (.000): ±.010  ANGLES: ±2°  SURFACE FINISH: 63RMS  BREAK ALL EDGES: .010015	DRAWN CHECKED	BM KH	09/26/2024	·			
			DATE STARTED IN PRODUCTION:		HPC600 Nipple x 3/4" Type M Male 30,000 psi				
			09/26/2024						
PROPRIETARY AND CONFIDENTIAL  THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF ULTRA PRESSURE COMPONENTS. ANY REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION OF		FILLETS & ROUINDS: R.015 - 0.30  THREADS UNIFIED CLASS 2A - 2B  CHAMFER THREADS 45° TO ROOT  30° CHAMFER IS OPTIONAL FOR MALE THREADS ONLY			ultraPressure		SIZE DWG. NO. REV  HPC600-1-M12		
ULTRA PRESSURE COMPONENTS IS PROHIBITED.	<u> </u>		We can handle Pressure		SCALE: 1.5:1 W	/EIGHT: 0.18	SHEET 1 OF 1		

4 3 2